



## Petroleum Delivery Units

**Standard specifications** may include:

- Semi-rectangular or oval shaped tank.
- Double or single bulkhead construction.
- Spring loaded mounting with full-length sills or bolster mount with rubber pads.
- Compartment lines with 3" internal valves and 3" piping to curbside, streetside or rear.
- Overturn rails full length, extruded.
- Two overturn drains with tubes running externally down front head.
- Fill opening 16" with 10" fills.
- Low profile 4 barrel boot at rear with hinged gate.
- Rear cabinet to accommodate installation of dual metering equipment with access out, side doors for both meter and reel. Hose door each side.
- Side cabinets for meters and reels, with or without doors.
- Fenders heavy gauged, polished aluminum.
- Bumper steel wrapped or heavy-duty rectangular box bumper at rear.
- Hose tubes.
- Lights all vapor proof.
- Natural aluminum finish or steel painted finish.

All specifications meet or exceed DOT MC-406 specifications.

**Optional specifications** may include:

- Rear or side delivery with or without bottom loading and vapor recovery.
- Dual or single pumping.
- Pre-piping for future bottom loading vapor.
- Air-operated internal valves.
- Open grating for equipment cabinets and barrel boot
- Vapor proof light for equipment cabinets.
- Compartment markers in each compartment.
- Tommy Lift Gate.
- Suction to rear 4 barrel boot.
- Gauge stick holder.
- 4" aluminum or steel compartment lines with air or cable internals.
- Aluminum fitting cabinet.

All specifications meet or exceed DOT MC-406 specifications.